
Date Printed 21.09.2018

Version number 1

Revision Date 21.09.2018



- GB



Date Printed 21.09.2018

Version number 1

Revision Date 21.09.2018

Trade name: Quick Drying Silver Paint

	(Contd. of page 1)
P103	Read label before use.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P241	Use explosion-proof [electrical/ventilating/lighting] equipment.
P303+P361+P353	FON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/regional/national/ international regulations.
· 2.3 Other hazards	S
Results of PBT a PBT: Not applicable	nd vPvB assessment
• vPvB: Not applica	

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:

• •		
CAS: 108-10-1	4-methylpentan-2-one	60.0%
	♦ Flam. Liq. 2, H225; ♦ Acute Tox. 4, H332; Eye Irrit. 2, H319; STOT SE 3, H335	

• Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

\cdot 4.1 Description of first aid measures

· General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

No adverse effects are anticipated from inhalation.

- After skin contact: Immediately rinse with water.
- After eye contact: Rinse opened eye under running water. If symptoms persist, consult a doctor.
- · After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed
- No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents: Water fog dried resin only.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- \cdot 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

(Contd. on page 3)

GB —

(Contd. of page 2)

agar scientific

Safety data sheet

according to 1907/2006/EC, Article 31 Version number 1

Revision Date 21.09.2018

Trade name: Quick Drying Silver Paint

· 5.3 Advice for firefighters

Date Printed 21.09.2018

• Protective equipment: Positive pressure self-contained breathing apparatus.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective gloves and glasses.
- · 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.
- 6.4 Reference to other sections See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- Information about fire and explosion protection:
 The dried resin is combustible, similar to wood. Burning dry resin emits dense, black smoke. As latex, material is not combustible.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- \cdot Further information about storage conditions:
- Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

• 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· Additional information about design of technical facilities: No further data; see item 7.

- · 8.1 Control parameters
- Ingredients with limit values that require monitoring at the workplace:

108-10-1 4-methylpentan-2-one

WEL Short-term value: 416 mg/m³, 100 ppm Long-term value: 208 mg/m³, 50 ppm Sk, BMGV

Ingredients with biological limit values:

108-10-1 4-methylpentan-2-one

BMGV 20 µmol/L

- Medium: urine
 - Sampling time: post shift

Parameter: 4-methylpentan-2-one

• Additional information: The lists valid during the making were used as basis.

(Contd. on page 4)

ĠВ



Date Printed 21.09.2018

Version number 1

Revision Date 21.09.2018

Trade name: Quick Drying Silver Paint

(Contd. of page 3)

· 8.2 Exposure controls · Personal protective equipment: General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Avoid contact with the eyes. Avoid contact with the eyes and skin. Respiratory protection: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device. · Protection of hands:

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of guality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection:



Tightly sealed goggles

9.1 Information on basic physical and chemical properties General Information			
Appearance:			
Form:	Fluid		
Colour:	According to product specification		
Odour:	Characteristic		
Odour threshold:	Not determined.		
pH-value:	Not determined.		
Change in condition			
Melting point/freezing point:	Undetermined.		
Initial boiling point and boiling range: 117 °C			
Flash point:	16 °C		
Flammability (solid, gas):	Not applicable.		
Ignition temperature:	460 °C		



Date Printed 21.09.2018

Version number 1

Revision Date 21.09.2018

Trade name: Quick Drying Silver Paint

	(Contd. of page 4)
 Decomposition temperature: 	Not determined.
· Auto-ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Explosion limits: Lower: Upper:	1.4 Vol % 8 Vol %
· Vapour pressure at 20 °C:	21 hPa
 Density at 20 °C: Relative density Vapour density Evaporation rate 	4.6806 g/cm ³ Not determined. Not determined. Not determined.
 Solubility in / Miscibility with water: 	Not miscible or difficult to mix.
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity: Dynamic: Kinematic:	Not determined. Not determined.
 Solvent content: Organic solvents: VOC (EC) 	60.0 % 60.00 %
Solids content: · 9.2 Other information	40.0 % No further relevant information available.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- Acute toxicity
 Harmful if inhaled

· LD/LC50 values relevant for classification:	

108-10-1	4-methyl	pentan-2-one

	LD50	2,080 mg/kg (rat)
Dermal	LD50	16,000 mg/kg (rab) 8.3-16.6 mg/l (rat)
Inhalative	LC50/4 h	8.3-16.6 mg/l (rat)

• Skin corrosion/irritation Based on available data, the classification criteria are not met.

· Serious eye damage/irritation

Causes serious eye irritation.

(Contd. on page 6)

GB

Date Printed 21.09.2018

Version number 1

Revision Date 21.09.2018

Trade name: Quick Drying Silver Paint

- (Contd. of page 5)
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- CMR effects (carcinogenity, mutagenicity and toxicity for reproduction) • Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure

May cause respiratory irritation.

- \cdot STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- \cdot 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- Additional ecological information:

· General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

• Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information		
· 14.1 UN-Number	UN1263	
· ADR, IMDG, IATA	011203	
 14.2 UN proper shipping name 		
· ADR	1263 PAINT mixture	
·IMDG	PAINT mixture, MARINE POLLUTANT	
	PAINT mixture	
· 14.3 Transport hazard class(es)		
· ADR, IATA		
· Class	3 Flammable liquids.	
	(Contd. on pag	



Date Printed 21.09.2018

Version number 1

Revision Date 21.09.2018

Trade name: Quick Drying Silver Paint

	(Contd. of page
· Label	3
· IMDG	
· Class · Label	3 Flammable liquids. 3
 14.4 Packing group ADR, IMDG, IATA 	II
 14.5 Environmental hazards: Marine pollutant: 	Symbol (fish and tree)
 14.6 Special precautions for user Danger code (Kemler): EMS Number: Stowage Category 	Warning: Flammable liquids. 33 F-E, <u>S-E</u> B
 14.7 Transport in bulk according to An of Marpol and the IBC Code 	nex II Not applicable.
· Transport/Additional information:	
 ADR Limited quantities (LQ) Excepted quantities (EQ) Transport category Tunnel restriction code 	1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 m 2 D/E
 IMDG Limited quantities (LQ) Excepted quantities (EQ) 	1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 m
· UN "Model Regulation":	UN 1263 PAINT MIXTURE, 3, II

SECTION 15: Regulatory information

 \cdot 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- · Directive 2012/18/EU
- Named dangerous substances ANNEX I None of the ingredients is listed.

Seveso category P5c FLAMMABLE LIQUIDS

- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- \cdot Qualifying quantity (tonnes) for the application of upper-tier requirements $50{,}000\ t$
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge and should assist the user with the safe handling of this material when properly applied. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

GB -

agar

Safety data sheet according to 1907/2006/EC, Article 31

Version number 1

Revision Date 21.09.2018

Trade name: Quick Drying Silver Paint

Date Printed 21.09.2018

	(Contd. of page 7)
Relevant phrases H225 Highly flammable liquid and vapour. H319 Causes serious eye irritation. H332 Harmful if inhaled. H335 May cause respiratory irritation.	
Department issuing SDS: Sales department Contact: sales@agarscientific.com Tel: +44 (0) 1279 813 519 Abbreviations and acronyms: ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agree International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic	ement concerning the
vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids – Category 2 Acute Tox. 4: Acute toxicity – Category 4 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3	G