

Safety data sheet

according to 1907/2006/EC, Article 31

Date Printed 10.01.2022

Version number 1

Revision Date 10.01.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier** AGC807
- **Trade name:** **Wenol Metal Polish**
- **Article number:** AGC807
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the preparation:** Cleaner for preparing samples for microscopy.
- **1.3 Details of the supplier of the safety data sheet**
- **Supplier.**
Agar Scientific Ltd
Parsonage Lane
Stansted CM24 8GF
United Kingdom
sales@agarscientific.com
Tel: +44 (0) 1279 813 519
- **Further information obtainable from:** Technical Support
- **1.4 Emergency telephone number:** 24 hours: +44 (0)1856 407333

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



skull and crossbones

Acute Tox. 3 H331 Toxic if inhaled.



health hazard

Muta. 1B H340 May cause genetic defects.

Carc. 1B H350 May cause cancer.

STOT RE 1 H372 Causes damage to the central nervous system through prolonged or repeated exposure.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



corrosion

Eye Dam. 1 H318 Causes serious eye damage.



Skin Irrit. 2 H315 Causes skin irritation.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Date Printed 10.01.2022

Version number 1

Revision Date 10.01.2022

Trade name: Wenol Metal Polish

(Contd. of page 1)

· Hazard pictograms


GHS02 GHS05 GHS06 GHS08

· Signal word Danger

· Hazard-determining components of labelling:

 Abrasive material (Al₂O₃)

White Spirit 150/200N

ammonia, anhydrous

Mineral oil (Kerosene)

· Hazard statements

H226 Flammable liquid and vapour.

H331 Toxic if inhaled.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H340 May cause genetic defects.

H350 May cause cancer.

H372 Causes damage to the central nervous system through prolonged or repeated exposure.

H304 May be fatal if swallowed and enters airways.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P321 Specific treatment (see on this label).

P331 Do NOT induce vomiting.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P362+P364 Take off contaminated clothing and wash it before reuse.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· Information concerning particular hazards for human and environment:

Appearance: Slightly red, pinkish paste.

Immediate effects: Irritant.

Potential health effects

Primary Routes of entry: Ingestion and skin contact.

Signs and Symptoms of Overexposure: ND

Eyes: May cause irritation and conjunctivitis. Dry dust may cause irritation.

Skin: Repeated or prolonged exposure may cause defatting of skin leading to irritation and dermatitis.

Ingestion: May cause irritation.

Inhalation: Repeated and prolonged exposure to high concentrations of vapor may result in central nervous system damage. When vapor pressure is low there are no adverse effects. Dry dust may form respirable particulates if disturbed.

Chronic Exposure: ND

Chemical Listed As Carcinogen Or Potential Carcinogen: None

See Toxicological Information (Section 11)

Potential environmental effects

See Ecological Information (Section 12)

· 2.3 Other hazards
· Results of PBT and vPvB assessment
· PBT: Not applicable.

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Date Printed 10.01.2022

Version number 1

Revision Date 10.01.2022

Trade name: Wenol Metal Polish

(Contd. of page 2)

 · **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

 · **Description:** Mixture of substances listed below with nonhazardous additions.

· **Dangerous components:**

CAS: 1344-28-1 EINECS: 215-691-6	Abrasive material (Al ₂ O ₃) ⚠ Acute Tox. 4, H332	27.0%
CAS: 8008-20-6 EINECS: 232-366-4	Mineral oil (Kerosene) ⚠ Asp. Tox. 1, H304	
CAS: 64742-82-1 EINECS: 265-185-4	White Spirit 150/200N ⚠ Muta. 1B, H340; Carc. 1B, H350; STOT RE 1, H372; Asp. Tox. 1, H304	14.0%
CAS: 68603-42-9	Coco fatty acid diethanolamide ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	9.0%
CAS: 7664-41-7 EINECS: 231-635-3	ammonia, anhydrous ⚠ Acute Tox. 3, H331; ⚠ Skin Corr. 1B, H314; ⚠ Aquatic Acute 1, H400; Flam. Gas 2, H221; Press. Gas (Comp.), H280	3.0%

 · **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· **General information:**

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Remove breathing equipment only after contaminated clothing have been completely removed.

In case of irregular breathing or respiratory arrest provide artificial respiration.

· **After inhalation:**

Supply fresh air or oxygen; call for doctor.

No adverse effects are anticipated from inhalation.

Remove to fresh air and rest until symptoms resolve. If irritation persists, seek medical advice.

· **After skin contact:**

Wash with water and soap and rinse thoroughly.

Wash with water until soapiness is removed.

· **After eye contact:**

Rinse opened eye for several minutes under running water. Then consult a doctor.

Flush eyes immediately with copious amounts of water for at least 15 minutes. If irritation persists, seek medical attention.

· **After swallowing:**

Do not induce vomiting Give water to drink to wash the alkaline product into stomach. Milk may be used to reduce the irritant effects of kerosene. Seek medical advice.

· 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

 · **5.1 Extinguishing media** Flash Point: >50 °C

· **Suitable extinguishing agents:**

Dry foam, dry chemical or water spray, carbon dioxide and sand or earth.

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Date Printed 10.01.2022

Version number 1

Revision Date 10.01.2022

Trade name: Wenol Metal Polish
(Contd. of page 3)

- **5.2 Special hazards arising from the substance or mixture**
 During heating or in case of fire poisonous gases are produced.
 Hazardous combustion products: Carbon monoxide, oxides of nitrogen, oxides of sulfur, and unburned hydrocarbons.
- **5.3 Advice for firefighters**
- **Protective equipment:**
 Positive pressure self-contained breathing apparatus.
 Wear self-contained breathing apparatus that is NIOSH approved. Use flooding quantities of water until well after fire is out.
- **Additional information**
 Organic dust particles in the atmosphere are combustible and may be explosive. Keep away from ignition sources.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
 Wear gloves.
 Wear protective gloves and glasses.
- **6.2 Environmental precautions:**
 Dilute with plenty of water.
 Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
 Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
 Use neutralising agent.
 Dispose contaminated material as waste according to item 13.
 Ensure adequate ventilation.
 Spillage of up to 5 liters may be mopped up with a cloth.
 Large Spills: If possible ventilate the area. The spillage should be placed into a suitable container for subsequent disposal.
- **6.4 Reference to other sections**
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
 Ensure good ventilation/exhaustion at the workplace.
 Open and handle receptacle with care.
 Prevent formation of aerosols.
 Use in well ventilated areas, wear suitable gloves if prolonged exposure is anticipated. Store in a cool, dry, frost free place, and out of reach of children and closed in original packs. Avoid contact with hot surfaces, organic vapors will be given off, and in an improperly ventilated area an explosion hazard could be created.
- **Information about fire - and explosion protection:**
 The dried resin is combustible, similar to wood. Burning dry resin emits dense, black smoke. As latex, material is not combustible.
 Protect against electrostatic charges.
 Extinguishing media: Water fog - dried resin only.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep container tightly sealed.

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Date Printed 10.01.2022

Version number 1

Revision Date 10.01.2022

Trade name: Wenol Metal Polish

(Contd. of page 4)

- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **8.1 Control parameters**
- **Additional information about design of technical facilities:** No further data; see item 7.

- **Ingredients with limit values that require monitoring at the workplace:**

7664-41-7 ammonia, anhydrous

WEL	Short-term value: 25 mg/m ³ , 35 ppm
	Long-term value: 18 mg/m ³ , 25 ppm

- **Additional information:** The lists valid during the making were used as basis.
- **8.2 Exposure controls** Ventilation required: Local mechanical exhaust.
- **Personal protective equipment:**
- **General protective and hygienic measures:**
 Keep away from foodstuffs, beverages and feed.
 Remove all soiled and contaminated clothing
 Wash hands before breaks and at the end of work.
 Store protective clothing separately.
 Avoid contact with the skin.
 Avoid contact with the eyes and skin.
- **Respiratory protection:**
 In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
 Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.
 Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**
 The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Penetration time of glove material**
 The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:**



Tightly sealed goggles

GB

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Date Printed 10.01.2022

Version number 1

Revision Date 10.01.2022

 Trade name: **Wenol Metal Polish**

(Contd. of page 5)

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Appearance:

Form:	Pasty
Colour:	Red
· Odour:	Ammonia-like
· Odour threshold:	Not determined.

· pH-value at 20 °C:	9.5
----------------------	-----

· Change in condition

Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	221 °C

· Flash point:	>50 °C
----------------	--------

· Flammability (solid, gas):	Not applicable.
------------------------------	-----------------

· Decomposition temperature:	Not determined.
------------------------------	-----------------

· Auto-ignition temperature:	Product is not selfigniting.
------------------------------	------------------------------

· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
-------------------------	---

· Explosion limits:

Lower:	0.6 Vol %
Upper:	6.1 Vol %

· Vapour pressure at 20 °C:	23 hPa
-----------------------------	--------

· Density at 20 °C:	1.15 g/cm ³
---------------------	------------------------

· Relative density	Not determined.
--------------------	-----------------

· Vapour density	Not determined.
------------------	-----------------

· Evaporation rate	Not determined.
--------------------	-----------------

· Solubility in / Miscibility with water:

Fully miscible.

· Partition coefficient: n-octanol/water:	Not determined.
---	-----------------

· Viscosity:

Dynamic:	Not determined.
Kinematic:	Not determined.

· Solvent content:

Water:	33.0 %
VOC (EC)	0.00 %

Solids content:	50.0 %
-----------------	--------

· 9.2 Other information	No further relevant information available.
-------------------------	--

SECTION 10: Stability and reactivity

· 10.1 Reactivity	No further relevant information available.
-------------------	--

· 10.2 Chemical stability	Stable under normal conditions.
---------------------------	---------------------------------

· Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

· 10.3 Possibility of hazardous reactions	No dangerous reactions known.
---	-------------------------------

· 10.4 Conditions to avoid	Temperatures in excess of 50 °C.
----------------------------	----------------------------------

· 10.5 Incompatible materials:	Strong oxidising agents.
--------------------------------	--------------------------

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Date Printed 10.01.2022

Version number 1

Revision Date 10.01.2022

Trade name: Wenol Metal Polish

(Contd. of page 6)

- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**

- **Acute toxicity**
Toxic if inhaled.

- **LD/LC50 values relevant for classification:**

64742-82-1 White Spirit 150/200N

Oral	LD50	5,000 mg/kg (rat)
------	------	-------------------

7664-41-7 ammonia, anhydrous

Oral	LD50	350 mg/kg (rat)
------	------	-----------------

Inhalative	LC50/4 h	2,000 mg/l (rat)
------------	----------	------------------

- **Specific symptoms in biological assay:**

- **Skin corrosion/irritation**

Causes skin irritation.

- **Serious eye damage/irritation**

Causes serious eye damage.

- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.

- **Additional toxicological information:**

- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**

- **Germ cell mutagenicity**

May cause genetic defects.

- **Carcinogenicity**

May cause cancer.

- **Reproductive toxicity** Based on available data, the classification criteria are not met.

- **STOT-single exposure** Based on available data, the classification criteria are not met.

- **STOT-repeated exposure**

Causes damage to the central nervous system through prolonged or repeated exposure.

- **Aspiration hazard**

May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

- **12.1 Toxicity**

This product contains 10-20 % of white spirit which is highly volatile and will rapidly evaporate to the air if released into the environment. Based upon data for similar materials, white spirit is classified as R51/53, toxic to aquatic organisms; may cause long-term adverse effects in the aquatic environment. Although data show that white spirit is not expected to persist in the aquatic environment, European Classification rules require that it be classified as potential hazard causing long-term adverse effects in the aquatic environment.

Chemical Fate Information: White spirit is expected to biodegrade rapidly and be "readily" biodegradable according to OECD guidelines. It can degrade rapidly in air and is expected to be removed in a waste water treatment facility.

- **Aquatic toxicity:** No further relevant information available.

- **12.2 Persistence and degradability** No further relevant information available.

- **12.3 Bioaccumulative potential** No further relevant information available.

- **12.4 Mobility in soil** No further relevant information available.

- **Additional ecological information:**

- **General notes:**

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Must not reach sewage water or drainage ditch undiluted or unneutralised.

Danger to drinking water if even small quantities leak into the ground.

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31

Date Printed 10.01.2022

Version number 1

Revision Date 10.01.2022

Trade name: Wenol Metal Polish
(Contd. of page 7)

- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Recommendation:** Disposal must be made according to official regulations.
- **Recommended cleansing agents:** Water, if necessary together with cleansing agents.

SECTION 14: Transport information

- | | |
|--|-----------------|
| · 14.1 UN-Number
· ADR, IMDG, IATA | -- |
| · 14.2 UN proper shipping name
· ADR, IMDG, IATA | Not restricted |
| · 14.3 Transport hazard class(es)
· ADR, IMDG, IATA
· Class | -- |
| · 14.4 Packing group
· ADR, IMDG, IATA | -- |
| · 14.5 Environmental hazards: | Not applicable. |
| · 14.6 Special precautions for user | Not applicable. |
| · 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code | Not applicable. |

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category**
H2 ACUTE TOXIC
P5c FLAMMABLE LIQUIDS
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 50 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 200 t
- **National regulations:**
- **Additional classification according to Decree on Hazardous Materials, Annex II:**
Carcinogenic hazardous material group III (dangerous).
- **Information about limitation of use:**
Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

(Contd. on page 9)

Safety data sheet

according to 1907/2006/EC, Article 31

Date Printed 10.01.2022

Version number 1

Revision Date 10.01.2022

Trade name: Wenol Metal Polish
(Contd. of page 8)

 · **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge and should assist the user with the safe handling of this material when properly applied. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H221 Flammable gas.
 H280 Contains gas under pressure; may explode if heated.
 H304 May be fatal if swallowed and enters airways.
 H314 Causes severe skin burns and eye damage.
 H315 Causes skin irritation.
 H319 Causes serious eye irritation.
 H331 Toxic if inhaled.
 H332 Harmful if inhaled.
 H335 May cause respiratory irritation.
 H340 May cause genetic defects.
 H350 May cause cancer.
 H372 Causes damage to organs through prolonged or repeated exposure.
 H400 Very toxic to aquatic life.

 · **Department issuing SDS:** Sales department

· Contact:

sales@agarscientific.com
 Tel: +44 (0) 1279 813 519

· Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
 IMDG: International Maritime Code for Dangerous Goods
 IATA: International Air Transport Association
 GHS: Globally Harmonised System of Classification and Labelling of Chemicals
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 VOC: Volatile Organic Compounds (USA, EU)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 PBT: Persistent, Bioaccumulative and Toxic
 vPvB: very Persistent and very Bioaccumulative
 Flam. Gas 2: Flammable gases – Category 2
 Press. Gas (Comp.): Gases under pressure – Compressed gas
 Flam. Liq. 3: Flammable liquids – Category 3
 Acute Tox. 3: Acute toxicity – Category 3
 Acute Tox. 4: Acute toxicity – Category 4
 Skin Corr. 1B: Skin corrosion/irritation – Category 1B
 Skin Irrit. 2: Skin corrosion/irritation – Category 2
 Eye Dam. 1: Serious eye damage/eye irritation – Category 1
 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
 Muta. 1B: Germ cell mutagenicity – Category 1B
 Carc. 1B: Carcinogenicity – Category 1B
 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
 STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1
 Asp. Tox. 1: Aspiration hazard – Category 1
 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

 · *** Data compared to the previous version altered.**