

Date Printed 02.02.2022 Version number 1 **Revision Date 02.02.2022**

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

· 1.1 Product identifier

Trade name: Crystalbond 555-HMP Adhesive Stick

· Article number: AGB7313

· 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance / the preparation: No data available

· 1.3 Details of the supplier of the safety data sheet

· Supplier.

Agar Scientific Ltd Parsonage Lane Stansted CM24 8GF United Kingdom sales@agarscientific.com

Tel: +44 (0) 1279 813 519

- · Further information obtainable from: Technical Support
- 1.4 Emergency telephone number: 24 hours: +44 (0)1856 407333

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



Acute Tox. 4 H302 Harmful if swallowed.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation. STOT SE 3 H335 May cause respiratory irritation.

- · 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms



GHS07

- · Signal word Warning
- · Hazard statements

H302 Harmful if swallowed.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

Keep out of reach of children. P102

P103 Read carefully and follow all instructions.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray. P280 Wear protective gloves / eye protection / face protection.

IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell. P301+P312

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

(Contd. on page 2)



Date Printed 02.02.2022 Version number 1 **Revision Date 02.02.2022**

Trade name: Crystalbond 555-HMP Adhesive Stick

(Contd. of page 1)

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· **PBT:** Not applicable. vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components: Void

· Additional information:

For the wording of the listed hazard phrases refer to section 16.

Primary Routes of entry: Eye, skin and inhalation.

Signs and Symptoms of Overexposure: ND

Eyes: May cause irritation, experienced as mild discomfort and seen as slight excess redness of the

Skin: Brief contact may cause slight irritation. Acute (short term) adverse effects are not expected from brief skin contact.

Ingestion: Moderately toxic. May cause abdominal discomfort, nausea, vomiting, and diarrhea.

Inhalation: Dust may cause irritation of the nose and throat. Overexposure to high concentrations of dust may cause respiratory irritation, experienced as coughing and difficulty breathing.

Chronic Exposure: No adverse effects have been documented in humans as a result of chronic exposure.

Chemical Listed As Carcinogen Or Potential Carcinogen: No

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours: therefore medical observation for at least 48 hours after the accident.

Primary Routes of entry: Eye, skin and inhalation.

After inhalation:

No adverse effects are anticipated from inhalation.

Remove from immediate source of exposure and assure that victim is breathing. If not breathing, administer cardio-pulmonary resuscitation (CPR). If breathing is difficult, administer oxygen if available. Seek medical attention.

After skin contact:

Wash with water and soap and rinse thoroughly.

Immediately wipe excess material off skin with a dry cloth then wash with plenty of soap and water for at least 5 minutes. Seek medical attention if irritation develops or persists. Remove contaminated clothing and shoes and clean thoroughly before re-use. Hot Fluid: Immediately cool skin with water and cold packs for at least 15 minutes. Do not put ice directly on skin. Do not attempt to remove solidified wax from the skin as severe tissue damage may result. Get immediate medical attention.

After eve contact:

Rinse opened eye under running water. If symptoms persist, consult a doctor.

Eye(s) Contact Hold eyelids open and flush with a steady, gentle stream of water for at least 15 minutes. Seek immediate medical attention, preferably with an ophthalmologist. If a physician is not immediately available, eye irrigation should be continued for an additional 15 minutes. Hot fluid product: Cool burns with plenty of low-pressure water and get immediate medical attention.

(Contd. on page 3)



Date Printed 02.02.2022 Version number 1 Revision Date 02.02.2022

Trade name: Crystalbond 555-HMP Adhesive Stick

(Contd. of page 2)

· After swallowing:

Call for a doctor immediately.

If swallowed, do not induce vomiting. If victim is conscious and alert, give 1-2 glasses of water to drink. Do not give anything by mouth to an unconscious person. Seek medical attention immediately. Do not leave victim unattended. To prevent aspiration of swallowed product, lay victim on side with head lower than waist. Vomiting may occur spontaneously. If vomiting occurs and the victim is conscious, give water to further dilute the chemical.

· Information for doctor:

Treatment: ND

Medical Conditions generally Aggravated by Exposure: Inhalation of product may aggravate existing chromic respiratory problems such as asthma, emphysema or bronchitis. Skin contact may aggravate existing skin disease.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

Use fire extinguishing methods suitable to surrounding conditions.

Use water spray, dry chemical, foam, or carbon dioxide to extinguish flames. Use water spray to cool fire-exposed containers. Water or foam may cause frothing.

5.2 Special hazards arising from the substance or mixture

Toxic levels of carbon monoxides, carbon dioxides, irritating aldehydes and ketones may be formed on burning. Heating in air may produce irritating aldehydes, acids and ketones.

5.3 Advice for firefighters

Firefighters should wear NIOSH/MSHA approved positive pressure breathing apparatus with full face piece and full chemical resistant protective clothing. Dike area to prevent runoff and contamination of water sources. Dispose of fire control water later.

Protective equipment:

Positive pressure breathing apparatus with full face piece and full chemical resistant protective clothing

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear chemical goggles, bodycovering protective clothing, chemical resistant gloves, and rubber boots. Use NIOSH approved respirator where mist occurs. Hot wax can cause burns to eyes and skin. Avoid breathing dust.

- · 6.2 Environmental precautions: Prevent entry into sewers and waterways.
- 6.3 Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Use vacuuming or sweeping compound for cleanup. Do not dry sweep or use methods that increase dusting. Prevent entry into sewers and waterways. Flush area with water to complete cleanup.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

GB



Date Printed 02.02.2022 Version number 1 Revision Date 02.02.2022

Trade name: Crystalbond 555-HMP Adhesive Stick

(Contd. of page 3)

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Avoid contact with eyes, skin and clothing. Avoid breathing dust and vapors generated when melted. Keep container closed. Promptly clean residue from closures with cloth dampened with water. Promptly clean up spills. Store in an area that is cool, dry, and well ventilated. Water contamination should be avoided. Store in clean plastic or steel containers.

- · Information about fire and explosion protection: No special measures required.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Storage temperature: Room temperature.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- · Additional information about design of technical facilities: No further data; see item 7.
- · Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

· Additional information: The lists valid during the making were used as basis.

· 8.2 Exposure controls

Use with adequate ventilation. If vapor, mist or dust is generated appropriate personal protection equipment and local ventilation controls must be employed.

- Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Airborne concentrations should be kept to lowest levels possible. If exposure limits are exceeded and local ventilation is unavailable, a supplied-air respirator or a self contained NIOSH-approved dust and mist respirator is required.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 5)



Date Printed 02.02.2022 Version number 1 Revision Date 02.02.2022

Trade name: Crystalbond 555-HMP Adhesive Stick

(Contd. of page 4)

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

Body protection:

Wear body-covering protective clothing.

Additional clothing and/or equipment: Safety shower and eyewash fountain.

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Appearance:

Form: Solid
Colour: Light yellow
Odour: Mild

· Odour threshold: Not determined.

· pH-value at 20 °C: 7

· Change in condition

Melting point/freezing point: 58-63 °C **Initial boiling point and boiling range:** Undetermined.

· Flash point: 275 °C

· Flammability (solid, gas): Not determined.

• **Decomposition temperature:** Not determined.

• Auto-ignition temperature: Product is not selfigniting.

• Explosive properties: Product does not present an explosion hazard.

· Explosion limits:

Upper: Not determined.

Not determined.

· Vapour pressure: Not applicable.

Density at 20 °C:
 Relative density
 Vapour density at 20 °C
 Evaporation rate
 1.08 g/cm³
 Not determined.
 >1 (air=1)
 Not applicable.

· Solubility in / Miscibility with

water: Soluble.

· Partition coefficient: n-octanol/water: Not determined.

· Viscosity:

Dynamic:Not applicable.Kinematic:Not applicable.

• 9.2 Other information No further relevant information available.

GB



Date Printed 02.02.2022 Version number 1 Revision Date 02.02.2022

Trade name: Crystalbond 555-HMP Adhesive Stick

(Contd. of page 5)

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability This material is stable under all conditions of use and storage.
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions Hazardous Polymerisation: Will not occur.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products:

Toxic levels of carbon monoxides, carbon dioxides, irritating aldehydes and ketones may be formed on burning. Heating in air may produce irritating aldehydes, acids and ketones.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity

Harmful if swallowed.

LD/LC50 values relevant for classification:

Oral LD50 5,000 mg/kg (rat)
Dermal LD50 >2,000 mg/kg (rabbit)

- Specific symptoms in biological assay:
- Skin corrosion/irritation

Causes skin irritation.

· Serious eye damage/irritation

Causes serious eye irritation.

- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- Other information (about experimental toxicology):

Skin (rabbit) Draize: > 0.50-3.00/8, slightly irritating.

Eye (rabbit) Draize: > 15.00-25.00/110, slightly irritating.

This product does not contain any compounds listed by NTP or IARC or regulated by OSHA as a carcinogen. This product may contain residual (less than 100 PPM) concentration of ethylene oxide. Ethylene oxide causes tumors in laboratory animals.

- Additional toxicological information:
- CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure

May cause respiratory irritation.

- STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes: Not known to be hazardous to water.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- vPvB: Not applicable.

(Contd. on page 7)



Date Printed 02.02.2022 Version number 1 Revision Date 02.02.2022

Trade name: Crystalbond 555-HMP Adhesive Stick

(Contd. of page 6)

· 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agents: Water, if necessary together with cleansing agents.

SECTION 14: Transport information

Void
Void
Void -
Void
No
Not applicable.
Not applicable.

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge and should assist the user with the safe handling of this material when properly applied. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Sales department
- · Contact:

sales@agarscientific.com Tel: +44 (0) 1279 813 519

· Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

(Contd. on page 8)



Date Printed 02.02.2022

Version number 1

Revision Date 02.02.2022

Trade name: Crystalbond 555-HMP Adhesive Stick

(Contd. of page 7)

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Acute Tox. 4: Acute toxicity – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

* Data compared to the previous version altered.